

SKIM COAT TOP GREY (388)



PRODUCT DESCRIPTION

ADX™ Skim Coat Top Grey (388) is a high-quality polymer modified cementitious skim-coat with excellent spreadability, adhesion performance, open time and non-powdery surface. It is designed specifically to be used on ADX™ Skim Coat Base for smooth interior wall or ceiling to receive wall covering or painting.

FEATURE & BENEFITS

- Excellent adhesion
- Good workability
- Good crack control
- Consistent quality
- Water resistant
- High durability

TECHNICAL DATA (typical values)

Appearance	Off white powder
Binder	Cement
Filler	Graded calcium carbonate powder
Auxiliaries	Additives and specialized polymers
Water Powder Ratio	0.46 – 0.47
Wet Density	1600 – 1700 kg/m ³
Dry Density	1200 – 1300 kg/m ³
Bond Strength	≥ 0.8 N/mm ²
Coverage	25kg bag - 20m ² 40kg bag - 32m ² at 1mm thickness
Packaging	25kg; 80bags per pallet 40kg; 50bags per pallet

SURFACE PREPARATION

1. Surface to be skimmed must be structurally sound, clean and free from dust, oil and any traces of foreign materials that may affect adhesion.
2. Highly absorptive surface to be moisten with water before skimming.

MIXING

1. Mix **ADX™ Skim Coat Top Grey (388)** with approximately 11.5L (25kg) / 18.4L (40kg) of clean water.
2. Mix thoroughly with an electrical mixer for 3-5 minutes to achieve lump-free homogeneous mortar paste.

APPLICATION

1. Apply **ADX™ Skim Coat Top Grey (388)** onto the prepared surface with a steel trowel.
2. Ensure the underneath layer is dry before application of subsequent layer.

PRODUCT LIMITATIONS

Do not use **ADX™ Skim Coat Top Grey (388)** over metal/steel or painted surface.

STORAGE

ADX™ Skim Coat Top Grey (388) should be stored in dry area free from excessive moisture.